

USB Headsets for Unified Communications



TECHNICAL DATA

| | |
|--------------------|-----------------------------|
| Microphone: | |
| Impedance: | 2.2kΩ |
| Sensitivity: | -32dB ± 3dB at 1kHz |
| Directivity: | Bi-directional |
| Frequency Range: | 50Hz~20kHz ± 6dB |
| Distortion: | Less than 3% |
| Power Supply: | 3V DC |
| S/N Ratio: | More than 58dB |
| Speaker: | |
| Impedance: | 150Ω ± 15% at 1kHz |
| Sensitivity: | 93 ± 3dB at 1kHz 60mV Input |
| Max Input Power: | 100mV |
| Frequency Range: | 100Hz~6800Hz |
| Distortion: | Less 3% at 1kHz 60mV |



JPL-400M-USB & JPL-400B-USB

Direct USB plug-in contact centre USB headset suitable for regular phone users. Simple plug & play - No software download needed.

Overview

| | |
|-----------------|--|
| Features | Single or dual ear Left / right ear side compatible Surround Shield™ noise cancelling microphone Wideband enabled speakers 'Put and stay' ratchet microphone boom arm Overhead, sure-fit fully adjustable headband Fitted with 55mm leatherette ear cushions for maximum all day comfort |
| What's included | Draw string headset storage bag, headset hanging hook, clothing clip and Quick Start Guide |
| Headset Weight | Mid-weight Headset, ~ 54g / ~78g |
| Connection | USB-A |
| Compatibility | Direct plug-in |
| Certifications | FCC, CE, RoHS, REACH |
| Warranty | 2 Years repair or replacement warranty |
| MOQ | Master Shipping Carton: 40 |
| Part Number: | JPL-400M-USB: 575-236-001, JPL-400B-USB: 575-236-002 |